

Float valve



Model 151

EN



To control the level of liquids in tanks, deposits, etc.

Specifications

- Nominal pressure: PN-16.
- Whitworth gas-tight male thread cylindrical connector ISO 228/1 1978 (DIN-259), from 3/8" to 2 1/2".

IMPORTANT

Depending on demand:

- Fluorelastomer closure (Viton), etc.
- Buoy with coating of Epoxy, PTFE (Teflón), Chemical nickel, Shining smooth, etc.
- Entirely Stainless steel (EN-1.4571).
(EN-1.4301), etc.

N°. PIECE	PIECE	MATERIAL		
		STAINLESS STEEL		
1	Body	Stainless steel (EN-1.4401)		
2	Coupling	Stainless steel (EN-1.4401)		
3	Closure	Silicone's rubber		
4	Nut	Stainless steel (EN-1.4401)		
5	Lever	Stainless steel (EN-1.4408)		
6	Pin	Stainless steel (EN-1.4401)		
7	Stem	Stainless steel (EN-1.4401)		
8	Connector	Stainless steel (EN-1.4401)		
DN		3/8" to 2 1/2"		
PN		16		
OPERATING CONDITIONS	PRESSURE IN bar	16	15	14
	MAXIMUM TEMP. IN °C	120	180	200
	MINIMUM TEMP. IN °C	- 60		

Closure pressure

The closure pressure of the valve will vary with relation to the specific weight of the liquid being controlled according to the following formula:

$$P = \frac{p}{p_a} P_a$$

P = Closure pressure liquid.
p = Specific weight liquid.

P_a = Closure pressure water.
p_a = Specific weight water.

R	REDUCED PITCH Ø	A	PRESSURE bar	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16																
				0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
3/8"	6	31	BUOY	C. Ø60x120				E. Ø90				E. Ø110								P.Ø150x60
			L	396				366				386								428
			H	215				210				225								222
			WEIGHT IN kgs.	0,38				0,41				0,50								0,60
			CODE	2008-151.3382				2008-151.3382 (+) 34005												
			FLOW l/h WATER 20°C	1058	1560	1780	2027	2270	2482	2603	2640	2794	2880	2970	3120	3250	3380	3510	3614	
1/2"	10	35	BUOY	C. Ø60x120		E. Ø90	E. Ø110	P. Ø150x60		E. Ø150										
			L	434		404	424	420		413										
			H	252		245	260				267									
			WEIGHT IN kgs.	0,53		0,56	0,64	0,90		0,84										
			CODE	2008-151.30221 (-) 34005		2008-151.30221				2008-151.30222										
			FLOW l/h WATER 20°C	2644	3738	4575	5287	5640	6346	7385	7457	7931	8354	8674	9051	9425				
3/4"	12,5	40	BUOY	E. Ø90	E. Ø110	P. Ø150x60		E. Ø150												
			L	450	469	509	507													
			H	240	255	250	282													
			WEIGHT IN kgs.	1,04	1,12	1,27	1,32													
			CODE	2008-151.3342																
			FLOW l/h WATER 20°C	4522	6395	7823	9044	10090	11033	11937	12797	13566	14289	14850						
1"	16	45	BUOY	E. Ø110	P. Ø150x60	P. Ø200x80		E. Ø150	E. Ø150	P. Ø250x95										
			L	475	507	565	510	615	732											
			H	257	250	275	285	327	350											
			WEIGHT IN kgs.	1,20	1,34	1,48	1,38	1,25	1,77											
			CODE	2008-151.31021				2008-151.31022												
			FLOW l/h WATER 20°C	6480	9270	11352	13148	14667	16044	17363	18369	19398	20510							
1 1/4"	21	50	BUOY	E. Ø150		P. Ø250x95		E. Ø200				P. Ø300x15								
			L	637		737		680				787								
			H	317		327		355				350								
			WEIGHT IN kgs.	1,82		2,21		1,95				2,72								
			CODE	2008-151.31421				2008-151.31422												
			FLOW l/h WATER 20°C	11508	16226	19925	23016	25663	28080	30382	32204	34136	36040							
1 1/2"	24	57	BUOY	P. Ø250x95		E. Ø200		P. Ø300x115		P. Ø350x130 or E. Ø300										
			L	660		610		710		760 or 710										
			H	285		315		310		330 or 385										
			WEIGHT IN kgs.	2,60		2,57		3,11		3,25 or 3,30										
			CODE	2008-151.3121		2008-151.3122														
			FLOW l/h WATER 20°C	14548	20512	25167	29070	32442	35362	38544	42216	46089	50200							
2"	29	60	BUOY	E. Ø200			P. Ø300x115		P. Ø350x130			E. Ø300								
			L	677			777		827			777								
			H	410			417		440			485								
			WEIGHT IN kgs.	3,86			4,39		4,81			4,87								
			CODE	2008-151.3202																
			FLOW l/h WATER 20°C	22136	31648	38296	44273	49364	54010	58439	63114	68030	72792							
2 1/2"	40	79	BUOY	E. Ø200		P. Ø300x115	P. Ø350x130 or E. Ø300													
			L	704		804	845 or 804													
			H	420		427	450 or 490													
			WEIGHT IN kgs.	6,52		7,30	7,72 or 7,50													
			CODE	2008-151.3222																
			FLOW l/h WATER 20°C	36015	50138	61128	70615	78342												

IMPORTANT

- C. - Cylindrical buoy.
- E. - Spherical buoy.
- P. - Flat buoy.
- Use the relevant code for the buoy, according to brochure Model 152.
- Buoys suitable for higher pressure are also suitable for use at lower pressure.

